

### **SPECIFICATION SHEET**

#### Aluminum Ladder

First scrub the ladder with oil to promise the ladder clean and good look. Then top&bottom both with strong master carton protect the ladder. Then Shrink packing with strong 0.6mm thickness PE film. Finally fasten the ladder with PP strape, make ladder no broken and easy loading and unloading. Ladder fittings refer to accessories other than the main material (aluminum alloy profiles, or insulated FRP profiles). The fittings and main materials are essential materials for a complete ladder. Aluminum ladder accessories mainly include guide teeth, flat ribs, diagonal ribs, ladder feet, rivets, handles, wax flag ropes, ladder hats, heads, hinges. Ladder fittings also play an important role in the ladder. The quality of the fittings directly affects the quality of a finished ladder.

No	Alloy	Thickness	Width	Length
1	6063-T5	Custimized	Custimized	Custimized

#### Chemical composition (%)

# Standard: GB/T 3190-2008

Grade	Si	Fe	Cu	Mn	Mg	Cr	Ni	Zn	Ti	AI
6063	0.20-0.6	0.35	0.10	0.10	0.45-0.9	0.10	-	0.10	0.10	Rest

## Mechanical Properties

Standard: GB/T 3880.2-2006

Alloy	Alclad classify	Temper	Sample Temper	Dimensions mm e3	Tensile strength R <sub>m</sub> /MPa	Yield strength R <sub>p0.2</sub> /MPa	Elongat A <sub>50mm</sub>	tion/% A <sub>5.65</sub>	Bending Radius <sup>*1</sup>
	Classify		remper	min eo		1xp0.2/1vii a	750mm	A5.65	T duius
6063 -			T5					-	
		T5		≤25	175	130	8	-	
								-	
	-			≤3				-	
				3 <e≤25< td=""><td>160</td><td>110</td><td>7</td><td>-</td><td></td></e≤25<>	160	110	7	-	
								-	

\*1 Coil samples bending 90°, t - thickness of coil

# **Physical Properties**

Property	Value	Unit
Density(20℃)	2.72	g/cm <sup>3</sup>
Melting Point	620-650	C
Thermal Expansion	23.5	(10-6K-1)(20/100℃)
Specific heat capacity	899	J/(Kg.K)( 0/100℃)
Modulus of Elasticity	70	GPa
Thermal Conductivity	205	W/(m. K) 20℃
Resistivity	32	nΩ .m

Formability	Weldability	Machinability	Corrosion Resistance
Very Good	Good	Very Good	Very Good



## **Specification**

Features: Foldable Ladder Rating: Type 1 - 250 lbs. Ladder Type: Step Ladder Load Weight Capacity (kg.): 80,100,120,130,150kg. Working height: 95/3.11'-590/15.07'cm/ft Closed height: 100/3.28'-600/18.00'cm/ft Thickness: 0.8mm,1mm,1.2mm,1.5mm,2mm

# **Products**



# Packing

Shanghai Metal Products are packed and labeled according to the regulations and customer's requests. Great care is taken to avoid any damage which might be caused during storage or transportation. In addition, clear labels are tagged on the outside of the packages for easy identification of the product I. D. and quality information. 1) Shanghai Metal Standard

2) Customization



Add: 20th Floor Yuan Mansion, 738 Donfang Road, Shanghai, China, 200122 Tel: +86 21 5830 9368, Fax: +86 21 5081 9492, Email: sales@shanghaiMetal.com